



Asian Laboratories

Construction Chemical Manufacturers



Committed to Superior Quality & Results



87,88, New Okhla Industrial Complex, DSIDC Shed, Scheme-1, Phase -II, New Delhi-110020  
t: 011-26386507,26386063 | Email: asianlab88@gmail.com

## PRODUCT INFORMATION: **ASIAN DE-BOND** ( **De-Bonding Agent for Concrete** )

### DESCRIPTION:

**ASIAN DE-BOND** is a emulsion of nano particles of spherical shape paraffin hydrocarbon. It forms a smooth film on spraying to the concrete surface. The film is impervious imparts good release

### PROPERTIES:

- Appearance : White Liquid
- Specific Gravity : 1.0 at 20°C
- Open Flash Point : More than 93°C
- Freezing Point : 0°C
- Viscosity : less that 10 CP at 20°C (Ostwald)

### ADVANTAGES:

- Provides barrier between concrete surfaces
- The film is non toxic & non hazardous
- The film can be used to protect the concrete surface from drying out and prevents shrinkage cracks on green concrete surfaces
- A single application is only required
- As the product is water based no special precaution are required for handling, storage or application.

### APPLICATION:

ASIAN De-Bond is a ready to use liquid compound, which should not be diluted with water. It can be applied by spray or by brush application on the concrete surface.

**COVERAGE:**

5.5 to 6.0 square meter per litre (200-300 sq.ft per gallon). It is essential not to apply the coating too thickly. While spraying the distance between the spraying device and the surface of the concrete should be approx, 1 m. Thus, a uniform coating is guaranteed, make sure that the spraying is properly carryout out.

PACKAGING: ASIAN De-Bond is supplied in 210 ltr drums

**Note:** This information is given in good faith, is based on results gained from experiences and tests. However, all recommendations or suggestion are made without guarantee since the conditions of use are beyond our control.

PRICE, PERIOD OF DELIVERY AND TERMS OF BUSINESS ON REQUEST  
**MANUFACTURED BY**

